

SF Coatings Safety Data Sheet

1. Product and Company Information

| Product Information | n | Company Information |
|---------------------|---------------------------|-----------------------------|
| Product Name: | SF Polyaspartic 80 Part B | SF Coatings |
| Product Type: | Polyurea Floor Coating | 717 Riverside Drive SE |
| Date MSDS Prepared: | 11/01/2020 | North Bend, WA. 98045 |
| Supersedes: | NA | Information: (425) 888-5565 |
| MSDS Prepared by: | jrc | |

*** 24 Hour Emergency Phone Number: Infotrac: 1-800-535-5053 ***

2. Hazards Identification

GHS Classification:

| Flammable Liquid | Category 3 |
|---------------------------------------|------------|
| Carcinogen | Category 2 |
| Target Organ (Central Nervous System) | Category 3 |
| Target Organ (Respiratory Irritant) | Category 3 |
| Aspiration Toxicant | Category 1 |
| Skin sensitization | Category 1 |

GHS Label Elements:

Hazard Symbols:



Signal Words: Danger

Hazard Statements:

H317 May cause an allergic skin reaction
H226 Flammable liquid and vapor
H304 May be fatal if swallowed and enters airways
H335 May cause respiratory irritation
H336 May cause drowsiness or dizziness
H351 Suspected of causing cancer

Precautionary Statements:

| Prevention: | P210 Keep away from heat/sparks/open floames/hot durfaces – No smoking |
|-------------|--|
| | P233 Keep container tightly closed |
| | P240 Ground/bond container and receiving equipment |
| | P241 Use explosion-proof electrical, ventilating, and lighting equipment |
| | P242 Use only non-sparking tools |
| | P243 Take precautionary measures against static discharge |
| | P260 Do not breathe dust/fume/gas/mist/vapours/spray |
| | P271 Use only outdoors in a well ventialted area |
| | P280 Wear protective gloves/protective clothing /eye protection/face protection |
| Response: | P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician |
| | P302+P352 IF ON SKIN (or hair): Wash with plenty of soap and water |
| | P304+P340 IF INHALED: Remove person to fresh air and get in a comfortable position |
| | P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact |
| | lenses, if present and easy to do. Continue rinsing. |
| | P333+P313 If skin irritation or rash occurs: Get medical advice/attention |
| Storage: | P405 Store locked up |
| Disposal: | P501 Dispose of contents/container in accordance with local/regional/national regulation. |
| = | |

3. Composition/Information on Ingredients

| Ingredient | Wt. Percent Range | CAS |
|---------------------------------------|-------------------|------------|
| Hexanethylene diisocyanate, oligomers | 60-80 | 28182-81-2 |
| Solvent Naptha | 10-30 | 64742-95-6 |
| 1,2,4-Trimethylbenzene | 5-20 | 95-63-6 |

4. First Aid Measures

Skin Contact: Remove contaminated clothing. Wash with soap and water. Seek medical attention if irritation occurs. Wash contaminated clothes separately before reuse.

Eye Contact: Remove contact lenses at once. Immediately flush with water for at least 15 minutes. Hold eyelids apart while rinsing. Seek medical attention if irritation persists.

Inhalation: Remove victim to fresh air. If not breathing, give artificial respiration. If symptoms persist, seek medical attention.

Ingestion: Do **NOT** induce vomiting. Get immediate medical attention. Never give something by mouth to an unconscious or convulsing person.

5. Fire Fighting Measures

 Flash Point:
 115°F
 Flammable Limits:
 LEL = 0.9
 UEL = 6.2

Extinguishing Media: Use foam, carbon dioxide, dry chemical or powders. Do not use water.

Fire Fighting Procedures: Full protective clothing and self contained breathing apparatus should be worn. Use water fine spray to cool containers. Ensure there is NO direct contact between the water and the product.

Unusual Fire and Explosion Hazards: Vapors are flammable and heavier than air. Vapors may travel across the ground and reach remote ignition sources causing a flashback fire danger.

Hazardous Decomposition Products: Carbon monoxide, carbon dioxide, nitrogen oxides.

6. Accidental Release Measures

Spill Response: Eliminate all ignition sources. Ventilate the area. Contain spill if possible, preventing entry into sewers and waterways. Absorb with an inert material such as dry sand or earth and place in a chemical waste container for disposal. Avoid combustible materials such as sawdust. Avoid personal contact.

7. Handling and Storage

Handling: Handle in a manner to minimize personal contact. Use only with adequate ventilation. Do not enter storage areas or confined spaces unless adequately ventilated.

Storage: Store at normal room temperature away from heat, sparks, and flames. Keep container tightly closed when not in use.

8. Exposure Control/Personal Protection

Exposure Limits

| Ingredient | ACGIH TLV | Oral LD 50 | Dermal LD 50 | Inhalation LC 50 |
|---------------------------------------|---------------------------|-----------------|-----------------|------------------|
| Hexanethylene diisocyanate, oligomers | 0.034 mg/m ³ | 746 mg/kg | >7000 mg/kg | 0.124 mg/l |
| Solvent Naptha | 100 mg/m ³ TWA | 3492 mg/kg | >3160 mg/kg | Not Established |
| 1,2,4-Trimethylbenzene | 25 mg/m ³ TWA | Not Established | Not Established | Not Established |

Personal Protective Equipment

Skin: Wear impervious gloves, clothing, and boots.

Eyes: Do not wear contact lenses. Wear safety glasses with side shield.

Respiratory: Use a properly fitting NIOSH/MSHA approved respirator with organic vapor cartridge.

Ventilation: Provide adequate ventilation, particularly in confined areas.

9. Physical and Chemical Properties

| Physical State: Liquid | Boiling Point: >300°F |
|-------------------------|--------------------------------------|
| Odor: Aromatic | Vapor Pressure: 0.269 kPa Hg at 20°C |
| Specific Gravity: 1.03 | Vapor Density: 4.2 |
| Volatile by Volume: 32% | Solubility in Water: Negligible |

10.Stability and Reactivity

Stability: Stable under normal conditions.

Hazardous Polymerization: Reacts with alcohols, amines, strong acids, water.

Conditions and Materials to Avoid: Extreme heat, open flame, moisture, ignition sources.

Hazardous Decomposition Products: Carbon monoxide, carbon dioxide, nitrogen oxides.

11.Toxicological Information

Chronic Exposure: Allergic reaction and skin sensitization.

Mutagens: Not expected to be a germ cell mutagen.

Teratogens:

Carcinogens: Tests caused cancer in laboratory animals, but the relevance to humans is uncertain.

No information available if blank.

12. Ecological information

Expected to be toxic to aquatic organisms. May cause long term effects in the aquatic environment.

13. Disposal Considerations

Dispose of in accordance with federal, state, and local regulations.

14. Transport Information

| | U.S. DOT | ΙΑΤΑ | International Maritime |
|----------------|------------------------|------------------------|------------------------|
| Shipping Name: | Paint Related Material | Paint Related Material | Paint Related Material |
| Hazard Class: | 3 | 3 | 3 |
| UN ID Number: | UN1263 | UN1263 | UN1263 |
| Packing Group: | 111 | 111 | 111 |

15.Regulatory Information

U.S. FEDERAL REGULATIONS:

This Material Safety Data Sheet (MSDS) has been prepared in compliance with the federal OSHA Hazard Communication Standard 29 CFR 1910.1200.

SARA 311/312 Hazard Class:

| Acute: | Yes |
|------------------|-----|
| Chronic: | Yes |
| Flammability: | Yes |
| Reactivity: | No |
| Sudden Pressure: | No |

SARA Reporting Requirements: The following components of this product are subject to the reporting requirements of Sections 304 and 313 of Title III of the Superfund Amendments and Reauthorization Act.

1,2,4,-Trimethylbenzene

SARA Threshold Planning Quantity: Not applicable.

U.S. STATE REGULATIONS:

Rule 66 Status: Not photochemically reactive

INTERNATIONAL REGULATIONS:

TSCA Inventory: All components of this product are in compliance with U.S. TSCA Chemical Substance Inventory Requirements.

Canada Domestic Substances List: All components of this product are listed on the Domestic Substances List

16.Other Information

| HMIS Codes: | HEALTH | 2 |
|-------------|------------|---|
| | Fire | 3 |
| | REACTIVITY | 1 |

For SAFETY DATA SHEETS, TECHNICAL DATA SHEETS, APPLICATION GUIDES and other information please visit: sfgaragefloors.com

